

**STATION APPROACH /
CHERITON ROAD
PHASE 2A – New drainage works**



Sapphire House | Clifton Lane | Runcorn | Cheshire | WA7 3FP
Office: 01928 751 761 | Fax: 01928 751 602 | Email: admin@batml.co.uk | Web: www.batml.co.uk



DO NOT SCALE FROM THIS DRAWING.
All measurements are in meters unless otherwise stated.

Signage to be agreed on site

- Traffic Management Notes:**
- 1) All temporary traffic management shall be in accordance with Chapter 8 of the Traffic Signs Manual 2016, Traffic Signs Regulations and General Directions 2013 and the Safety at Street Works and Road Works, A Code of Practice, 2013.
 - 2) All temporary traffic management locations are indicative to help clarity and are subject to approval from the on site client.
 - 3) All carriageway widths to be a minimum of 3.25m wide unless otherwise shown.
 - 4) This drawing has been specifically prepared to meet the requirements of the named client and may contain design or innovative features which differ from conventional design standards.
 - 5) Upon installation the TM Foreman is responsible for ensuring the design of the traffic management meets the on site requirements, Chapter 8 standards and any modifications as necessary.

Site location:		Station Approach, /Cheriton Road, Folkestone, Kent, CT20 2QN	
What 3 Words:	bleach.arise.hotdog	Phase 2A	
Traffic Management:	4 way temporary traffic control & Pedestrian management		
Authority:	Kent County Council		
Scale	Date	Drawn by	
@A3	07/05/2025	SB	
DWG no:	PHASE 2A - 4257 - SR - CR - New drainage works	Checked By	
Rev.	Description:	ZW	

CLIENT



- MULTI-PHASE TRAFFIC SIGNALS**
- 1 All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
 - 2 Maximum distance between any two temporary traffic signals to be 249m.
 - 3 Minimum distance between any two temporary traffic signals to be 30m.
 - 4 Temporary traffic signals shall not occur within 50m of an existing level crossing.
 - 5 Pelican crossing or signalised junction without the consent of the Engineer. The Engineer shall consult with the authority responsible for any of these types of facility prior to traffic management being installed in adjacent areas.
 - 6 Coning shall be installed at 45° to the edge of carriageway, as generally indicated.
 - 7 Multi-phase portable traffic signals shall operate in vehicle actuated (VA) mode at all times unless otherwise directed by the Engineer.
 - 8 Multi-phase portable traffic signals shall only be installed with the written permission of the local highway authority whose roads they are installed on.
 - 9 Cable crossing protectors and P7010/P7013 signs shall be provided whenever control cables cross a section of carriageway open to traffic.
 - 10 The signal control mechanism shall normally be placed in a location from which it is possible to view all approaches to the site.
 - 11 Duplicate primary signal to be installed as instructed.
 - 12 Lane width past the works to be 3.7m maximum, 3.25m desirable minimum, 3.0m absolute minimum.

